

---

## SILICONE OIL: TECHNICAL DATA SHEET

### 1. Description and main characteristics

Silicone Oil 50 cPs . Used to dilute silicone , change the hardness.

---

### 2. Main fields of application

- **Industrial field**
- 

### 3. Important recommendations

Close carefully the packaging.

---

### 4. Main Characteristics

Aspect	transparent
Dynamic Viscosity at 25°C	50 mPa.s
Density at 25°C	0,96 g/cm <sup>3</sup>
Tensile Strength	0,021 N/m
Flash Point	> 250 °C
Refraction Point a 25° C	Approx 1,403

### 5. Important recommendations

The surfaces with which the material enters in contact must be perfectly clean, free of grease and dry.

---

### 6. packaging

<i>Zhermack code</i>	<i>packaging</i>
<b>DT40030</b>	<b>5 KG</b>

---

### 7. Safety data sheets

The preparation is not to be considered hazardous in accordance with directive 88/379/CEE and subsequent amendments.

---

### 8. Shelf life

The delayer is guaranteed for a period of 18 months if stored correctly at a temperature of between 5° - 27°C (41° - 80°F).

---

### IMPORTANT OBSERVATIONS

**The advice given verbally, in writing or through demonstrations on the use of the products are based on our**



ZHERMACK S.P.A. HI - TECH DIVISION  
Via Bovazecchino, 100 – 45021 Badia Polesine (RO)  
Tel 0425.597611 - Fax 0425.53596

**knowledge. The use and application of the product by the user lie beyond the control of the company and are therefore the user's own responsibility.**